

Q16 - Engineering Directed Standard Tool/Perishable Tool Inspection Requirements

"IMPORTANT NOTICE: A hard copy of this document may not be the document currently in effect. The current version is always the version on the Lockheed Martin network."

* REVISED

** ADDED

I. APPLICATION

Except as otherwise directed by Buyer, the governing revision of this document shall be the revision in effect on the date of this Purchase Order (PO). Subject to limitation by Buyer, if any, if subsequent revisions of this Buyer document are issued, Seller is authorized to use the latest revision of this document. If Seller opts for use of the latest revision, Seller shall utilize the applicable portions of the latest revision in their entirety.

- * NOTE: As used herein, the term "Buyer" is synonymous with the term "LOCKHEED MARTIN", the terms "Purchase Order" and "PO" are synonymous with the term "Contract", the terms "Item" and "Items" are synonymous with the term "Work", and the term "Seller" is synonymous with the term "SELLER", all as may be used elsewhere in the PO of which this document "Q16 – Engineering Directed Standard Tool/Perishable Tool Inspection Requirements" is a part.


II. REQUIREMENTS

- A. Seller shall perform an inspection after all normal manufacturing operations have been completed. Seller shall perform this inspection of any Item prior to delivery to Buyer.
- B. Seller shall furnish the results of this inspection and any previous inspections to Buyer or Buyer's Representative upon request.
- C. Seller shall be permitted to perform sample inspection on the Items (reference Paragraph II. A.) as long as one (1) of the following statistically valid sampling plans is used.
 1. MIL-Std-105E

2. ISO 2859-1
 3. ANSI/ASQ Z1.4-2003
- * D. If Seller is other than an original equipment manufacturer of the Items, Seller shall furnish to Buyer or Buyer's Representative an electronic, non-proprietary monthly report that contains, but is not limited to, the following data elements from the final inspection:
4. Distributor (Source provider) if applicable
 5. Original Manufacturer
 6. LM Aero Part Number
 7. Total Lot Quantity
 8. Sample Quantity Inspected

Table 1 Buyer Site Inspection Requirements by Tool Category

	MARIETTA, MERIDIAN, & CLARKSBURG	FORT WORTH
	Body Diameter	Back Taper
	Damage Check	Cutting Diameter
	Flute Length	Damage Check
	Identification	Flute Length
	Material Type	Hardness
	Over-All-Length	Helix Angle
	Surface Treatment	Identification
	Thread Size	Material Type
	Key Characterisitcs	Over-All-Length
		Relief/Clearance Angles
		Run-Out (Concentricity)
		Surface Finish



	MARIETTA, MERIDIAN, & CLARKSBURG	FORT WORTH
	Reamer Diameter Hex Diameter and Length Seat Angle Pilot Diameter and Length	Chamfer Lip Height Pilot Diameter Pilot Length Margin Width Seat Angle Thread 2A Fit Core Diameter Concentricity of Pilot/Cutter/Shank Diameters
	Flute Configuration Shank Configuration End Configuration Corner Radius	Radial Rake Angle Shank Diameter Corner Radius Radius Mismatch Preset Flats Length/Depth Core Diameter End Concavity Radial/Axial Clearance
	Pilot Diameter/Pilot Hole Countersink Angle Pilot Length Seat Angle	Countersink Angle Relief/Clearance Angles Pilot Diameter Pilot Length Axial Rake Angle Seat Angle Thread 2A Fit Countersink/Pilot Radius
	Corner Radius Diameter Pilot Hole	Radial/Axial Rake Corner Radius Pilot Diameter Margin Width Flat/Perpendicular Cutting Edges
	Pilot Diameter Countersink Angle Seat Angle Drill Diameter	Countersink Angle Countersink Axial Rake Angle Transition Between Countersink and Drill (radius or counterbore) Lip Height Variation Chisel Edge Centrality Web Thickness (W2) Shank Diameter Margin Width Alignment of Secondary Cutting Edges Key Characteristics Identified by Drawing
	See Paragraph IV for Verification by Buyer	

	MARIETTA, MERIDIAN, & CLARKSBURG	FORT WORTH
Circular Saw Blades	Outside Diameter Arbor Hole Kerf Width Number of Teeth Magnetic Particle Inspection (per ASTM-E-1444)	
Hole Saws	Diameter End Configuration Arbor Threads	
Routers	Diameter End Configuration	
Bucking Bars	Surface Finish Hardness	
Drill & Reamer Bushings	Inside Diameter Outside Diameter Length	
Keller-Lok Bushings	Inside Diameter Outside Diameter Length	
Safety Apparel	Size Logo	
Process Tooling	Dimensional Check with Tape Measure or Equivalent	
Slings	Over-All-Length with Tape Measure or Equivalent	

D. Seller shall inspect the following characteristics by Standard Tool Number for the Marietta, Meridian, and Clarksburg facilities for the specific features identified below:

1. 550H006
Hole must be centered with no burrs per Buyer specification
2. 550H007
Dash number must match bushing size per Buyer specification
3. 550H008
Slot dimension = 0.141" +.002"/-.000"
4. 550H203
Surface coating adherence
Dash number location per Buyer specification

- * IV. TAPER-LOK DRILL AND REAMER VERIFICATION BY BUYER (Applies only to Items shipped by Seller to Marietta, Meridian or Clarksburg)
 - A. Seller shall submit a sample quantity of Taper-Lok drills and/or reamers to Buyer for verification. The verification process consists of the Buyer drilling and/or reaming holes to verify conformance to Engineering standards.
 - B. Seller shall ship the test samples to Buyer at no increase in Buyer's cost or fee.
 - C. Seller shall use the following guidelines to determine the proper quantity to be sent by Seller to Buyer for verification.
 - 1. Two (2) drill or reamers from the first 50 received and one (1) drill or reamer for every additional 50 (or portion of 50).
 - 2. The minimum quantity to be sent will be two (2) and the maximum quantity will be six (6).
 - * D. Seller shall complete the Tapered Cutter Verification Request form or a Buyer-approved alternate for submitting the samples to Buyer. The form may be accessed at: <http://www.lockheedmartin.com/material-management>. Highlight "Quality Requirements" and select "Forms". Seller shall submit an individual form, in triplicate, for each unique tool.
 - D. Seller shall contact the buyer of record on the Purchase Order for specific shipping instructions for each sample to be submitted for verification.
 - E. If and when Seller receives a completed and approved Tapered Cutter Verification Request form from Buyer, Seller shall ship the remaining quantity to Buyer.
 - F. If Buyer has documented a rejection on the Tapered Cutter Verification Request form, Seller may submit additional sample quantities to Buyer for verification. If Buyer documents rejection of the additional sample(s), the entire lot is rejected and is not suitable for use by Buyer.