		[redacted]	1. Highlight the special process 2. Select special processors 3. Select yourself as the special processor a. If your name does not show up as an approved processor, contact your LM buyer to have the hierarchy table updated. For additional information on how to use the ship-to-module, view the downloadable guide here.
			SUPPLIER REQUIREMENTS
QAQC04	Q		This clause mandates that all applicable requirements that are invoked or applied to the customer's purchasing document, including this clause, shall be flowed down to the organization's sub-tier suppliers.
QAQC24	Q		The contractor shall participate in the Government-Industry Data Exchange Program (GIDEP) in accordance with the requirements of the GIDEP S0300- BT-PRO-010 and S0300-BU-GYD-010, available from the GIDEP Operations Center, PO Box 8000, Corona, California 91718-8000. The contractor shall review all GIDEP ALERTS, GIDEP SAFE-ALERTS, GIDEP Problem Advisories, GIDEP Agency Action Notices, and NASA Advisories to determine if they affect the contractors products/services provided to NASA. For those that affect the program, the contractor shall take action to eliminate or mitigate any negative effect to an acceptable level. The contractor shall generate the appropriate failure experience data report(s) (GIDEP ALERT, GIDEP SAFE-ALERT, GIDEP Problem Advisory) whenever failed or nonconforming items, available to other buyers, are discovered during the course of the contract.
QC5	Q	CONTAMINATION CONTROL	Articles ordered under this Contract shall be cleaned by the Contractor as required by the Lockheed Martin contamination control specifications. Cleaning and/or testing of the articles shall be performed in facilities w

QM8	Q	PRINTED WIRING BOARD FABRICATION REQUIREMENTS	Fabrication requirements per 3GPS-RQ-09-0080, for rigid boards, or 3GPS-RQ-09-0081, for flex and rigid flex boards, are invoked on this order. In the event of a conflict between 3GPS-RQ-09-0080 or 3GPS-RQ-09-0081 and the drawing, the drawing shall take precedence.
QPS	Q	ENGINEERING PURCHASE	

QQD4K3	Q	QUALITY PROGRAM REQUIREMENTS (ANSI/NCSL Z540.1)	The Contractorôs Calibration System shall conform to the requirements of the elements described in ANSI/NCSL Z540.1, either part 1 or part 2, and is subject to review and approval at all times by Lockheed Martin.. Third party registration by an accredited registrar will be accepted. Contractor declaring system compliance to ANSI/NCSL Z540.1 with no formal accredited registrar, will be reviewed. The Contractorôs system will be subject to review and approval at all times by Lockheed Martin. The Contractorôs signed certification must state (1) traceability to the National Institute of Standards and Traceability, (2) tool or gage number, and (3) Contract number.
QQD4K6	Q	ISO 17025 ï TEST FACILITY REQUIREMENTS	The Contractorôs Laboratory shall conform to the requirements of the elements described in ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories. Third party registration by an accredited registrar will be accepted. A Contractor declaring compliance to ISO/IEC 17025 with no formal accredited registrar will be reviewed by Lockheed Martin. The Contractorôs system will be subject to review and approval at all times by Lockheed Martin. The Contractor shall maintain test control systems that confirm Lockheed Martin hardware meets test requirements listed on the order. Lockheed Martin may inspect all deliverable items before, during or after test, before shipment or during final inspection and acceptance at destination. Lockheed Martin may require repair or rework of any deliverable item that fails to meet requirements. Rejected items may be submitted during or after testing but

Contract, drawings, specification and other applicable documentation that all process certifications, chemical and physical test reports, are on file at this facility and are available for review by Lockheed Martin."

A. The identity and unit weight of explosive(s);

			identified within a designated section of the controlling specification for items being procured under the contract line item of this Purchase Order.
NON-CONFORMANCE / CHANGE PERFORMANCE			
Q1Z	Q	SUPPLIER NON-CONFORMANCE REQUIREMENT INSTRUCTIONS	Submit the following to LM: 1.Proposed changes to LM-approved technical, supplier configuration or supplier process requirements. 2. Material, parts or assemblies that donô meet Procurement Order requirements via Supplier Request for Information or Change (VRIC). A Subcontract or Purchase Order Change Notice will list each LM-approved change and/or LM Material Review Board action(s).
Q3Z	Q	SUPPLIER ñRED FLAGò TIMELY	

QTM5	Q	REJECTED MATERIAL RESUBMISSION	Any items under this order which are rejected by Buyer and returned to Supplier for repair or replacement will be returned to Supplier on a shopper or consignment order which indicates, ñSupplier Responsibilityò, ñBuyer Responsibilityò, or ñResponsibility Unknownò. Such items shall either be replaced or reworked to specification and resubmitted to Buyer. When an LM Discrepancy Report (DR) or Nonconformance Report (NCR) IS FORWARDED TO Supplier with rejected items, the DR or NCR number shall be entered on Supplierôs shipping document. Supplierôs shipping documentation shall include : (i) a statement detailing the corrective action taken to prevent recurrence of the cause of rejection or recommended action to avoid further rejection if cause of rejection is

Q1B	Q	DATA REQUIRED WITH EACH SHIPMENT	If a lot is split and a partial shipment is made, all required data shall accompany each shipment. An additional copy of the data (i.e. test data, certificates of conformance, etc.) must be included in the follow-on shipments. When samples or sample data are sent separately, they must reference the original purchase order number, line item, and date of shipment. If a partial shipment is made, annotate it on the shipper.
QAQC06	Q	AQC06 CERTIFICATE OF COMPLIANCE	

QB2B	Q	SUPPLEMENTAL DATA REQUIREMENTS

			that appropriate Government inspection planning can be accomplished. If your facility is not serviced by Government inspection and/or the area Government inspection representative or agency cannot be located, immediately notify Customer. NOTE: Do not proceed with fabrication/manufacture processing until Government mandatory inspection points (GMIPs) are added to Organization's manufacturing planning. GMIPs shall not be by-passed unless authorized in writing by the Government inspection representative. Organization shall request and include the documents specified in the Government delegation, in the shipment. The Government's request for source inspection shall specify the period and method for the advance notification and the Government representative to whom it shall be furnished. Request shall not require more than 2 workdays of advance notification if the Government representative is in residence in the Contractors plant, nor more than 7 workdays in other instances. Organization, without additional charge to the procurement document, shall provide all reasonably required facilities and assistance (applicable drawings, specifications, change orders, inspection and/or test equipment) for the US Government representative to perform their duties. Organization shall ensure that Government inspection acceptance is evident for every individual GMIP and that completion of Government inspection is evident on Organization's shipping document/packing list. Evidence may be the signature of Government inspection representative with printed name and office, or application of the representative's stamp. The Government shall accept or reject supplies as promptly as practical after delivery, unless otherwise provided in the contract. Government failure to inspect and accept or reject the supplies shall not relieve the Contractor from responsibility, nor impose liability on the Government, for nonconforming supplies. When manufacturing processing affected by GMIPs is subcontracted by Organization, the provisions of this Clause shall be included in the Organization's Purchase Order verbatim.
QAQC14	Q	QAQC14 CUSTOMER SOURCE INSPECTION (CSI)	Customer source inspection is required prior to shipment of articles from the Organization's facility. Upon receipt of this Order and prior to commencing work, promptly notify the Customer's Procurement Quality Assurance Representative (PQAR) assigned to the Organization's facility so the appropriate inspection plan can be coordinated. The supplier shall use EXOSTAR to arrange source inspection. The supplier may view a source inspection request process document using the following link: http://www.lockheedmartin.com/content/dam/lockheed/data/corporate/documents/suppliers/spacedoc/spacedoc-request-source-insp.pdf In the event that a Procurement Quality Assurance Representative does not normally service the Organization's facility, immediately notify the Customer Procurement representative to obtain a point of

			contact for the appropriate Procurement Quality Assurance Representative (PQAR) assignment. Source inspection shall be conducted by the Customer at the Organizationôs facility or where designated in the Order. The Organization shall notify PQAR office a minimum of five (5) working days in advance of the time the articles or materials are ready for inspection or test. The Organization shall make available to the PQAR all applicable drawings, specifications, procedures, statements of work, Customerôs Order, test software, and changes thereto, related inspection and/or test equipment, and such other information as may be required to satisfactorily perform the inspections and tests required under this Order.
QAQC14A	Q	QAQC14 CUSTOMER SOURCE	

			The First Article(s) shall be produced on production equipment and using processes which will be utilized on production runs. Additionally, the Organization shall perform additional First Article Inspection(s) per the requirements of AS9102 (i.e.: following every major tooling, every design change, and subsequent to any evident quality degradation for a specified part or article). Records of all first article activity will be documented as required in AS9102, treated as quality / acceptance records, and made available to Customer if requested.
QCF	Q	GOVERNMENT SOURCE INSPECTION C OF C	Hardware listed in this Purchase Order (PO) has Mandatory Government Source Inspection requirements, Classification of Characteristics (CC's). Supplier must contact local Defense Contract Management Agency (DCMA) Quality Assurance Representative, prior to start of production, to coordinate with DCMA the mandatory inspections. All CC inspection characteristics must be included in the shop travelers before starting production and include a space for DCMA to buy-off (stamp or physical/electronic signature) at each attribute. If a Navy Gage is used at your facility for the verification of a hardware feature, then the Gage(s) must be maintained in accordance with OD60758, Procedure-Receipt, Care and Shipment of Navy Special Interface Gages. See enclosure to this PO for the list of CC's. The enclosure, sent out as a part of this PO, is the governing document unless superseded by a Purchase Order Change Notice. If the CC listing is not an enclosure in this PO it must be obtained from DCMA. Note: Only those CC's attributes that are affected in a Rework/Repair/SLE PO shall require re-inspection and require a space in the shop traveler for DCMA stamp or physical/electronic signature.
QCV	Q	FACILITY ENGINEERING SOURCE INSPECTION	LM source inspection is required at the manufacturing plant. Contact LM Facility Engineering at (321) 476-7382 between the hours of 0730800 and 1615 00 EPST for direction and scheduling of source actions as required.
QPWB3	Q	PWB CONFORMANCE INSPECTION - THIRD PARTY	Inspection of conformance coupons shall be completed prior to LM Final Source inspection and prior to [redacted] manufacturer facility. Coupon inspection shall be performed by a Program approved Third Party

[redacted] 158 MCID 18 <</MCID 18>

When mixed lot / date codes are authorized, the shipping document shall list individual lot / date codes and quantity. Multiple lot / date codes shall not be co-mingled. In addition, the individual part containers shall be

			be pre-coordinated with your Lockheed Martin Buyer. When mixed date/lot codes are authorized, the shipping document shall list individual date/lot codes and quantity. Multiple lot/date codes shall not be co-mingled.
QT12	Q	SUPPLIER RETAIN TEST DOCUMENTATION TWELVE YEARS	Supplier shall retain test reports/inspection records/evidence of acceptance for a minimum of twelve (12) years from the date of delivery.
QT7	Q	SUPPLIER RETAIN TEST DOCUMENTATION SEVEN YEARS	Supplier shall retain test reports/inspection records/evidence of acceptance for a minimum of seven (7) years from the date of delivery.
QT9	Q	PWB PROCUREMENT DOCUMENT REQUIREMENTS	Printed wiring boards shall meet the requirements and Engineering Purchasing Specification(s) listed in the Procurement Document (PD). Quality records (i.e. material certifications, test data, mounts, coupons, etc.) shall be retrievable, within 24 hours after a request by LM, for 3 years after closure of this PD. Notify LM when the 3 year retention period expires and request further direction.
QVT	Q	SUPPLIER RETAIN TEST DOCUMENTATION FIVE YEARS	Supplier shall retain test reports/inspection records/evidence of acceptance for a minimum of five (5) years from the date of delivery.
QVT6	Q	SUPPLIER RETAIN TEST DOCUMENTATION SIX YEARS	Supplier shall retain test reports/inspection records/evidence of acceptance for a minimum of six (6) years from the date of delivery.

QZ25	Q	F120014	F120014, LOA Btwn LMSC & Teledyne Wah-Chang Albany Pertaining to Procurement Rqmts for D5 PBCS Manifold
QZ250	Q	D915705	D915705, PA Quality Requirements for Trident II Batteries
QZ251	Q	D915706C	D915706C, PA Quality Rqmts for Printed Circuit Boards, Multilayer Boards, Rigid Flex Master Interconnect Board & Flex Cables
QZ252	Q	D915709P	D915709P, PAQR - Black Box Subcontractor Piece Part Rqmts
QZ256	Q	D915711	D915711, Addendum 2 - to Supplier Tech Program Management LMSC/915710A
QZ257	Q	D915720	LMSSC D915720, Supplier Technical Program Management (STPM) Document for Test Missile Telemetry & Tracking System (including Addendum 1 and Addendum 2) applies.
QZ261	Q	D915722	D915722, PA Quality Requirements for Instrumentation Electronic Packages
QZ262	Q	D915723	D915723, PA Quality Rqmts for Transducers and Instruments
QZ265	Q		

QZ300	Q	D824158-15	D824158-15, DRD - FTS Filter Crystal Assembly
QZ302	Q	SMP010787U06	SMP010787U06, LOA between LM and IRC (Division of TRW) pertaining to STPM D824156 and STPM SMP010760U05
QZ303	Q	SMP010707U05	SMP010707U05, PAQR for G&H PMM Connectors (changes from D915703-1, Rev C)

QZ76	Q	F120199

	Added: QA10	CLASS 1 or CLASS 2 Changes; GPS3 Program Specific
	Added: QSQAP	QPS3 Quality Assurance Plan; GPS3 Program Specific
	Edited: QAQC09	Included approval requirements for Calibration System.
10/5/2009	Added: QT4F	Counterfeit EEE Part Avoidance, Detection, Mitigation, Disposition (SAE AS5553)
2/16/2010	Edited: QZ72, QZ318	Edited clause text to align with document text
	Edited: QZ109	Edited clause title and text to align with document text
5/4/2010	Added: QM8	3GPS-RQ-09-0080 and 3GPS-RQ-09-0081 for GPS111 for PWB
	Added: QB12	Certificate of Compliance for Subcontract Tin Mitigation
	Updated: QA7	Requirement clarification
5/11/2010	Edited: Q0W	Minor language edits
7/19/2010	Removed: QDV	Code Deactivated
7/26/2010	Added: QLMPC	LM Supplied Paint Coupon Requirements
11/16/2010	Added: QTC7	LMSSC Procured Parts/Materials Counterfeit Avoidance
	Added: QT4A	Quality System Requirements (SAE AS9120)
	Edited: QTC6	Clarified Electronic (EEE) Parts
	Edited: QNOWGC	Clarified method of delivery of documentation
1/24/2011	Edited: QLM	Typo correction
1/28/2011	Edited: QZ152	Title Change
2/21/2011	Removed: QAQC32, QB8, QBN, QBQ, QC3, QD6, QD7, QD11, QE6, QE8, QET, QER, QES, QEU, QEW, QEX, QF5, QF6, QF8, QN5, QYJ, QYN, QYP, QYQ, QYU, QYR, QYV, QYZ, QZ2, QZ26, QZ29, QZ36, QZ67, QZ68, QZ70, QZ114, QZ115, QZ116, QZ117, QZ119, QZ122A, QZ123, QZ124, QZ129, QZ130, QZ133, QZ135, QZ158, QZ159, QZ168, QZ169, QZ175, QZ176, QZ177, QZ178, QZ198, QZ199, QZ203, QZ205, QZ233, QZ236, QZ239, QZ240, QZ242, QZ243, QZ245, QZ247, QZ254, QZ255, QZ258, QZ259, QZ264, QZ272, QZ288, QZ289, QZ290, QZ291, QZ292, QZ293, QZ294, QZ295, QZ296, QZ297, QZ298, QZ301	Codes Deactivated
	Added: QZ322	SMP01720U11 ï FBM Specific
	Added: QPMT	LM861793 Test Report AEHF Specific
3/3/2011	Edited: QLM	Edited to add clarification

3/8/2011	Edited: QZ204, QZ238, QZ241, QZ253, QZ257, QZ263, QZ271	Minor FBM Code edits
3/9/2011	Removed: QZ184, QZ190, QZ195	Codes Deactivated
5/3/2011	Removed: QZ44, QZ45, QZ46, QZ57, QZ71, QZ74, QZ75, QZ89, QZ97, QZ98, QZ102	Codes Deactivated
7/22/2011	Removed: QTS	Replaced with QQTS
	Added: QQTS	Pind Inspection Required
	Added: QA2C	Orion Government Source Inspection
	Added: QVP	

3/8/2013	Added: QQ32A	*Added duplicate codes to accommodate required changes for P2P Use Replacement for Q32A
	Added: QTC2A	PreCap Inspection - for use with non-material procurement activity (similar to QAQC14A)
3/19/2013	Added: QV15	THAAD First Article Inspection ï (QAQC15 with additional text regarding notification)
	Added: QD4K7	Quality Program Requirements (ANSI/NCSL Z540.3)
4/18/2013	Updated: QV15	FAI Production Lapse Clarification
5/21/2013	Updated: QPMT	Removed CoC submittal to a source inspector
6/5/2013	Updated: QZ152	Additional clarification regarding A268126 requirements for FBM
7/21/2013	Added: QQZ6	Duplicate text for QZ6 to correct P2P setup error
8/26/2013	Edited: QZ99	Replaced the word "transformer" with "transducers" for FBM
10/9/2013	Removed: Commercial Q-Codes	No longer in use by Space Systems
10/25/2013	Edited: QQWGC	Added referral to EDSS (Electronic Data Supplier Submittal)
12/12/2013	Removed: QTC7	Code Deactivated
	Updated: QTC6	Counterfeit Q1 0 0 1 72.05 564.45 Tm(t)-21(43.24T/F4 10 Tf1 0 0 1 631.4 421.35 Tm0 (

Updated: QZ320 Added: Q4M	QZ320 updated to replace SMP010762U08 with SMP10764U09