

LMSSC PACKAGING STANDARD

P-43
Revision 2
Page 1 of 4
09-02-2008

IDENTICAL PARTS WITH ENDS SEALED OR PLACED IN SEALED PLASTIC BAG


1.0 SCOPE

P-43

Revision 2

Page 2

09-02-2008



4.0 QUALITY ASSURANCE

4.1 Packaging shall be accomplished in such a manner as to prevent physical damage to, or degradation of, the packaged items during delivery to the using activity. It shall be the prerogative of LMSSC to return damaged items, at supplier's expense, when such damage is attributable to improper or inadequate protection.

5.0 NOTES

5.1 The following information is intended as a guide or aid to suppliers in meeting the requirements of this specification:

5.1.1 DEFINITION – Unprotected Silver Surfaces. All metallic silver surfaces (having stringent reflectivity or conductivity requirements, close-tolerance finishes and/or dimensions, without supplementary tarnish-resistant treatment), the deterioration of which may result in premature failure or malfunction of the item or equipment having such surfaces.

5.1.2 REFERENCES

Commodity

Military/Commercial Specification

Box, Corrugated

ASTM D5118, Type CF, Class Domestic, SW, Style, RSC, Grade 44 ECT or 200 Mullen

Box, Wood

ASTM D6880

Box, Wood, Cleated

ASTM D6251

Cushioning, Cellular Plastic

PPP-C-795, Class 2

Cushioning, Cellulosic

A-A-1898, Grade 1, Class C, Style 1, Size L, Kraft Backed

Protective Caps

AS-90376 or NAS 831; NAS 813, 820